

# SteelWalk



Aquastop®



OVP



Stainless steel **drive-over bar available in many different optics** (including WallWasher) **and finishes**, or with RGB LED for evocative colour effects. Also controllable using the DMX protocol, it is fitted with IP68 push-fit connectors.

**Passive heat dissipation**

AISI 316 stainless steel casing for high salinity environments

**Light management**


Four optics available ensuring maximum design flexibility

**Anti-vandal**

Installation with outer casing fitted with anti-vandal screws



## SteelWalk On/Off | Linear profiles | 180-300 V | powerLED 12 W 630 mA



## type

Steel CRI 80 **93668**

## colour

3000 K	1248 lm	<b>W</b>
4000 K	1332 lm	<b>N</b>
5000 K	1518 lm	<b>C</b>
R - G - B - Y on request		

## optic

15°	<b>15</b>
30°	<b>30</b>
60°	<b>60</b>
Wall W.	<b>25</b>




98137

Cables

Outer casing 722 - 723

## SteelWalk On/Off | Linear profiles | 180-300 V | powerLED 24 W 630 mA



## type

Steel CRI 80 **93671**

## colour

3000 K	2496 lm	<b>W</b>
4000 K	2664 lm	<b>N</b>
5000 K	3036 lm	<b>C</b>
R - G - B - Y on request		

## optic

15°	<b>15</b>
30°	<b>30</b>
60°	<b>60</b>
Wall W.	<b>25</b>




98138

Cables

Outer casing 722 - 723

## SteelWalk On/Off | Linear profiles | 180-300 V | powerLED 48 W 630 mA



## type

Steel CRI 80 **93674**

## colour

3000 K	4992 lm	<b>W</b>
4000 K	5328 lm	<b>N</b>
5000 K	6072 lm	<b>C</b>
R - G - B - Y on request		

## optic

15°	<b>15</b>
30°	<b>30</b>
60°	<b>60</b>
Wall W.	<b>25</b>




98139

Cables

Outer casing 722 - 723

## SteelWalk DMX | Linear profiles | 190-250 V | powerLED 12 W 630 mA



## type

Steel CRI 80 **93669**

## colour

3000 K	1248 lm	<b>W</b>
4000 K	1332 lm	<b>N</b>
5000 K	1518 lm	<b>C</b>
R - G - B - Y on request		

## optic

15°	<b>15</b>
30°	<b>30</b>
60°	<b>60</b>
Wall W.	<b>25</b>




98137



Cables

Outer casing 722 - 723

## SteelWalk DMX | Linear profiles | 190-250 V | powerLED 24 W 630 mA



## type

Steel CRI 80 **93672**

## colour

3000 K	2496 lm	<b>W</b>
4000 K	2664 lm	<b>N</b>
5000 K	3036 lm	<b>C</b>
R - G - B - Y on request		

## optic

15°	<b>15</b>
30°	<b>30</b>
60°	<b>60</b>
Wall W.	<b>25</b>




98138



Cables

Outer casing 722 - 723

## SteelWalk DMX | Linear profiles | 190-250 V | powerLED 48 W 630 mA



## type

Steel CRI 80 **93675**

## colour

3000 K	4992 lm	<b>W</b>
4000 K	5328 lm	<b>N</b>
5000 K	6072 lm	<b>C</b>
R - G - B - Y on request		

## optic

15°	<b>15</b>
30°	<b>30</b>
60°	<b>60</b>
Wall W.	<b>25</b>




98139




Cables

Outer casing 722 - 723

**SteelWalk DMX RGB** | Linear profiles | 190-250 V | powerLED 36 W 630 mA





type	colour	optic
Steel	93673	RGB
		Z
		15°
		15
		30°
		30
		60°
		60
		Wall W.
		25



722 - 723

**SteelWalk DMX RGB** | Linear profiles | 190-250 V | powerLED 60 W 630 mA



type	colour	optic
Steel	93676	RGB
		Z
		15°
		15
		30°
		30
		60°
		60
		Wall W.
		25



722 - 723